



ARMSTRONG CHEMICALS PVT. LTD.,
Bengaluru
An ISO 9001 Certified Company

CONPROOF RMC ADMIX[®] 88

High Performance Water Reducing
Crack Resistant Waterproofing Free Flow RMC Admix

DESCRIPTION OF THE PRODUCT :

Conproof RMC Admix is High Performance water Reducing Crack Resistant waterproofing Free Flow RMC Admix to eliminate the cracks and Improves High Bond Strength between Concrete and Steel.

RECOMMENDED :

To mix in the RMC Transit Mixer after reaching the site, continuously mix for a 3 to 5 minutes and unload the concrete wherever to pour the same.

Minimises maximum extent the risk of RMC concrete issues

Pour **Conproof RMC Admix** Liquid 100 ml. in the mixing water required for one bag (50 kgs.) cement and stir properly. Make concrete/ cement-sand mix as usual with this water. **Conproof RMC Admix** is an excellent product with consistent high quality, best suitable for making complete waterproofing of concrete & cement, sand mix. It is ideal to use as an excellent waterproofing admixture in **Ready Mix Concrete** for water retaining structures like swimming pools, reservoirs, water tanks & basements, roof slabs, screeds, bathrooms, toilets, external wall plasterings etc. **Conproof RMC Admix** an multi dimensional product.

ADVANTAGES :

- Reduces the Hydration with in the fresh concrete and minimizes crack formation.
- High quality and highly dependable waterproofing
- Excellent workability and cohesiveness of the mix.
- Efflorescence Resistant
- Improves high bond strength between concrete & steel.



METHOD OF APPLICATION :

Conproof RMC Admix has to be mixed in the transit mixer at the site at the dosage of 100ml per bag of 50 kgs. Cement (for 6 Cubic Mrtr. load in a transit mixer approx. 4.2 ltrs. to 5 ltrs. to be added and rotated for 3 - 4 Minutes before unloading the concrete

HEALTHY & SAFETY PRECAUTIONS :

Contamination with skin and eyes should be washed with water. CONPROOF RMC ADMIX should be kept away from children and animals. Prolonged inhalation of the vapor should be avoided and adequate ventilation be ensured

DOSAGE :

100 ml per Bag of 50 Kgs. Cement.

PACKING : 1, 5, 20 & 210 Ltrs.

STORAGE & SHELF LIFE :

Shelf life is 24 months from the date of manufacturing in unopened condition .Store in cool & dry place.

Whilst **ARMSTRONG CHEMICALS PVT. LTD.** strives to ensure that any advice, information or recommendation given are appropriate and correct. It cannot accept any liability directly or indirectly arising out of the use of products since the method and place of application of the products are beyond its control.

ARMSTRONG CHEMICALS
TRUSTED AND ACCLAIMED FOR ITS
MULTIPLE ACTION PERFORMANCE



Authorised Distributor / Stockist



Manufacturers :

ARMSTRONG CHEMICALS PVT. LTD.

An ISO 9001 Certified Company

Regd. Off : 36/1, G-5, New International Airport Road, Ganga Nagar, BENGALURU - 560 032.

e-mail : armstrongchemicals@gmail.com; Web : www.acpl.live | www.armstrongchemicals.in

Please Contact for Customer Care Information : **08095621122** | Toll Free No. **1800 103 2034**