



ARMSTRONG CHEMICALS PVT. LTD., Bengaluru
An ISO 9001 Certified Company



INTERIOR
EMULSION
PAINT

High Performance High Shine Interior Emulsion Paint

DESCRIPTION OF THE PRODUCT :

Shineshield interior emulsion is a special types of co- polymers and fine pigments available with special additives like anti-fungal, anti-algae, anti- fading, to get optimum dispersion level etc . It gives excellent durability for interior walls.

RECOMMENDED :

- Used for interior wall surface, plasters, brick, asbestos, ceilings etc.

ADVANTAGES :

- VOC
- Long lasting
- Quick drying.
- Good washability.
- Economical product with optimum performance.
- Ease of Application.
- It delivers more whiteness in comparison to other products in the category making the walls look fresher and cleaner.
- Smooth and pleasing Finish.
- Anti fungal additives prevents growth of Fungus, Bacteria.

TECHNICAL DATA

1.	Colour	White base - whatever the shades require, it can be achieved by mixing of stainers
2.	Drying- time surface dry	30 min
3.	Gloss levels	Smooth Finish
4.	Washable	Moderate
5.	Flash point	NA
6.	Thinning	50% BY Volume using water
7.	VOC IN G/KG OR G /L	< 50 g /L
8.	Dry film thickness (in microns) /coat	25 -30 microns
9.	Fire hazard class	Non- flammable
10.	Number of Coats required	Apply 2 coats of Shineshield Emulsion

SURFACE PREPARATION :

Surface should be absolutely dry and free from dirt, dust, rust, loose paint, loose particles, damaged plaster, oils, fungus and algie by means of cleaning the surface with wire brush and water wash. Acid etching has to be done if required, before water wash.

PRIMER :

For both freshly plastered or repainting surface, apply one coat of Apply the RAINPROOF CP / RAINPROOF WP primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours. Apply using brush/roller/spray and allow it to dry for 6 to 8 hours .

Before Coating : Scrip all the old paints and remove all the loose particles before starting the above process.

DIRECTION FOR APPLICATION :

Dilute the SHINESHIELD INTERIOR EMULSION paint as per the recommended dilution ratio and strain with thin cloth. Apply First Coat of SHINESHIELD Interior Emulsion by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.

TOPCOAT APPLICATION : Dilute 1 litre of SHINESHIELD Interior Emulsion paint with 500-600 ml of water and apply 2-3 coats of topcoat to ensure good hiding. A gap of 4-6 hours to be given after each coat to dry. Application can be done by brush/roller/spray

COVERAGE :

Anormal masonry surface after brushing **FIRST COAT** 220 to 280 Sq.ft. / Ltr.

SECOND COAT 120 to 140 Sq.ft./ltr.

Coverage depends on roughness and porosity of surface.

PACKING : 1, 4, 10 & 20 Ltrs.

SHELF LIFE & STORAGE :

The product has shelf life of 24 months from the date of manufacturing, if stores in original packing and temperature between 10°C to 30°C.

Whilst **ARMSTRONG CHEMICALS PVT. LTD.** strives to ensure that any advice, information or recommendation given are appropriate and correct. It cannot accept any liability directly or indirectly arising out of the use of products since the method and place of application of the products are beyond its control.

Authorised Distributor / Stockist

ARMSTRONG CHEMICALS
TRUSTED AND ACCLAIMED FOR ITS
MULTIPLE ACTION PERFORMANCE



Manufacturers :

ARMSTRONG CHEMICALS PVT. LTD.

An ISO 9001 Certified Company

Regd. Off : 36/1, G-5, New International Airport Road, Ganga Nagar, BENGALURU - 560 032.

e-mail : armstrongchemicals@gmail.com; Web : www.acpl.live | www.armstrongchemicals.in

Please Contact for Customer Care Information : **08095621122** | Toll Free No. **1800 103 2034**