



ARMSTRONG CHEMICALS PVT. LTD., Bengaluru
An ISO 9001 Certified Company

RAPIDSTRONG SF[®] SALT FRUSHER

Efflorescence Resistance Primer
(Formerly known as Roofcare Salt Frusher)

DESCRIPTION OF THE PRODUCT :

RAPIDSTRONG SF - SALT FRUSHER - is especially pigmented coating which act as Anti efflorescence primer and prevent growth of salt formation on the wall.

FEATURES :

- Excellent alkali & efflorescence resistance
- Physical barrier to water transport
- Chemical barrier to salt migration
- Excellent substrate penetration & over coat adhesion.

ADVANTAGES :

- Long life, High-class appearance of topcoat
- Minimize the re-painting requirements
- Ideal for high alkaline concrete
- Prevention of top coat defects

TYPICAL APPLICATION :


- To be applied over concrete, Plastered or brick, Masonry surfaces.

RECOMMENDED :

- It is an ideal material recommended for RCC structure. Masonry walls, Sloping / Flat Roofs, Cooling tower & Bridges.

FEATURES & BENEFITS :

- Water borne product, Eco friendly, Single component, ease of application. Provides excellent efflorescence resistance due to its chemical inertness. Based on chemically inert polymers hence suitable for high alkaline substrates. Provides deep penetration thus imparts excellent substrate adhesion. Used as a primer on internal and external, surfaces. Long term exterior durability.



TYPICAL CHARACTERISTICS :

Nature	:	Single component, liquid
Color	:	Turbid white
Specific gravity at 30°C	:	1.10 ± 0.02%
Viscosity on ford dup B4	:	75 - 80 sec
Intercoat interval	:	4 to 6 Hrs.
Dilution	:	50% potable water
Coverage	:	55-60 Sq.ft. per 2 coats / Ltr.
DFT per coat	:	30 - 40 Microns

DIRECTIONS FOR USE :

Clean the surface with brush and ensure no loose particle remains on substrate. On the clean and dry substrate apply FIRST Coat with the help of brush. Application to be done till saturation level achieves. Allow it to dry for 1-2 Hrs. then apply SECOND coat. On the top of that, after 24 Hrs. can be applied any required paint coatings.

CLEANING OF TOOLS AND EQUIPMENT :

Tools and equipment can be easily cleaned with water. If dries it should be scrapped off.

PACKAGING 5, 10 & 20 Ltrs.

SHELF LIFE Two years from the date of Manufacturing

STORAGE : In order to preserve all the properties, store the material in the original un-opened containers in cool and dry place.

Whilst **ARMSTRONG CHEMICALS PVT. LTD.** strives to ensure that any advice, information or recommendation given are appropriate and correct. It cannot accept any liability directly or indirectly arising out of the use of products since the method and place of application of the products are beyond its control.



Manufacturers :
ARMSTRONG CHEMICALS PVT. LTD.

An ISO 9001 Certified Company

36/1, G-5, New International Airport Road, Ganga Nagar, BENGALURU - 560 032.

e-mail : armstrongchemicals@gmail.com |

Web : www.acpl.live | www.armstrongchemicals.in



Please Contact for Customer Care Information : **08095621122** | Toll Free No. **1800 103 2034**

Authorised Distributor / Stockist

ARMSTRONG CHEMICALS
TRUSTED AND ACCLAIMED FOR ITS
MULTIPLE ACTION PERFORMANCE

ARMSTRONG

